SAFETY DATA SHEET

OCEAN STATE WAYLUBE 32



Identification Section

1.1 Product Identifiers

OCEAN STATE WAYLUBE 32 Product Name

Product Code(s)

1.4 Supplier Information

Ocean State Oil 123 Ocean State Drive North Kingstown, RI 02852

Phone: 800-554-4557 Fax 401-295-4110

1.2 Product Usage

Recommended Usage:

Ways LubricantNot Intended for any other usage **Restricted Usage**

1.3 Emergency Support

Emergency Support : CHEMTREC

> +1(800) 424-9300 United States +01 (703) 527-3887 International

Section **Composition / Information on Ingredients**

Classification of the Substance or the Mixture

GHS Rating(s) Signal Word

2.2 **Label Elements** No Classified Hazards.

Precautionary : P201 Obtain Special Instructions Before Use.

> Do Not Handle Until All Safety Precautions Are Understood. P202

P281 Use Personal Protective Equipment As Required.

If Exposed Or Concerned: Get Medical Advice/attention. Response : P308

Storage Store Locked Up. : P405

Disposal Dispose Of Container According To Regional Regulations. : P501

2.3 **Other Hazards**

Ocean State Waylube 32 Issued: 5/1/2015 Revised: 7/29/2015 Page 1 / 7

Section 3 - Hazards Identification

3.1 Substance Details

Chemical Name	CAS#	%Weight
BASE OIL SEVERELY REFINED	64742-65-0	90.0
RESIDUAL OILS, PETROLEUM, SOLVENT-DEWAXED	64742-62-7	6.0
LUBRICATING OILS, PETROLEUM, HYDROTREATED	64742-58-1	2.0

INERT The remaining percentage are not listed as Physical or Health Hazards (29 CFR 1910.1200) 2.0

Products containing mineral oil with less than 3% DMSO extract as measured by IP-346.

0 11	4		Place Ald March
Section	4	-	First Aid Measures

4.1 First Aid Measures

Eye Contact: Immediately flush eyes with plenty of water occasionally lifting the upper and lower eyelids.

Check for and remove any contact lenses. Continue to rinse for atleast 20 minutes. Get

Medical Attention.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing

is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth to mouth

resuscitation. Maintain an open airway. Get medical attention if symptoms occur.

: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the

lungs. Never give anything by mouth to an unconscious person. get medical attention if

symptoms occur.

4.2 Symptoms & Effects

Ingestion

To Physician : Treat symptomatically. Contact poison specialist if product has been ingested.

Specific Treatment : No Specific Treatment.

4.3 Medical Attention

Protection of First Aiders : No action should be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Note To Doctor : Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation

of stomach contents is necessary, use method least likely to cause aspiration.

Ocean State Waylube 32 Issued: 5/1/2015 Revised: 7/29/2015 Page 2 / 7

Section **Fire Fighting**

Extinguishing Media

Suitable Media **Unsuitable Media**

: CO2, Dry chemical, or Foam. Water can be used to cool and protect product. Do not use water jet as an extinguisher, it will spread the fire.

Specific hazards arising from this product

: When heated, hazardous gases may be released including: sulfur dioxide. A solid stream of water will spread the burning material. Material creates a special hazard because it floats on water. This material creates a special hazard because it floats on water. This material is harmful to aquatic life. Any fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Firefighters Advice 5.3

Special protective equipment

: Fire Equipment Information: Fire-fighters should wear appriovirate protective equipment and sel contained breathing apparatus(SCBA) with a full face -piece operated in positive pressure mode.

Accidental Release Measures Section 6

6.1 Personal precautions, protective equipment

General Measures

: No health affects expect from the cleanup of this material if contact can be avoided. Follow personal protect equipment recommendations found in section 8 of this SDS.

6.2 **Environmental Precautions**

Non-Emergency Personnel: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform authorities if the product has caused environmental pollution Water Polluting Material may be harmful to the environment if released in large quantities.

6.3 Materials & Methods to Contain and Cleanup

Reference Section 8

: Follow all protective equipment recommendations provided in Section 8.

Spill Control Measures

: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center.

Containment and Cleanup: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillage's with noncombustible, absorbent material e.g. sand earth vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via licensed waste disposal contractor. Contaminated absorbent material may pose the same threat hazard as the spilled product.

Issued: 5/1/2015 Revised: 7/29/2015 Page 3 / 7 Ocean State Waylube 32

Section 7 - Handling & Storage

7.1 Safe Handling

Personal Protective Equipment

: Put on appropriate personal protective equipment (see section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, keep lid tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

7.2 Safe Storage

Required conditions

: Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 113 deg F (45 deg C) for extended periods of time or if heat sources in excess of 250 deg F (121 deg C) are used. Store away from incompatible materials. See section 10 for incompatible materials.

7.3 Specific End Use

Designed Purpose

: This product is designed for use as a Ways Lubricant

Section 8 - Exposure Control

8.1 United States Exposure Limits					
CAS	Chemical Name	Exposure Limits	Source		
64742-65-0	Distillates, petroleum, solvent-dewaxed heavy paraffinic	5mg/m3	IUCLID		

8.2 Exposure Controls

Engineering Controls

: Material should be handled in enclosed vessels and equipment, in which case general room ventilation should be sufficient. Local exhaust ventilation should be used at points where dust, mist, vapors or gases can escape into the room air. No special requirements under ordinary conditions of use and with adequate ventilation.

Enviromental Exposure Controls

: General room ventilation should be satisfactory. Local exhaust ventilation may be necessary if misting is generated.

Hygeine Measures

: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

Eye / Face Protection

: If contact is likely, safety glasses with side shields are recommended.

Skin / Hand Protection

: Butyl rubber. Use nitrile or neoprene gloves. Use good industrial hygiene practices. In case of skin contact, wash hands and arms with soap and water. Use caution when opening manway covers of storage and transportation containers. 3-nitroaniline crystals may be present on the interior surface of these openings. 3-nitroaniline is toxic by dermal exposure.

Respiratory Protection

: Use a properly fitted air purifying or supplied air respirator complying with an approved standard if a risk assessment indicates this a necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Ocean State Waylube 32 Issued: 5/1/2015 Revised: 7/29/2015 Page 4 / 7

Section 9 - Physical & Chemical Properties

9.1 Information On Basic Physical and Chemical Properties

Physical state : Liquid Color : B&C

Odor : Characteristic of Petroleum

Odor threshold: No Data AvailablepH: No Data AvailableFreezing Point: No Data AvailableBoiling Point / Range: No Data Available

Flash Point COC : 221C

Evaporation rate: : No Data Available
Upper Explosive Limits (% air) : No Data Available
Lower Explosive Limits (% air) : No Data Available
Flammability (solid, gas) : Not Applicable
Vapor pressure : <1 mm Hg

Vapor density (air=1) :> 1 Specific Gravity : 0.89

Auto-ignition temperature: Not DeterminedDecomposition temperature: Not DeterminedSolubility in water: Negligible, 0-1%Partition coefficient, n-octanol/water: No Data Available

Section 10 - Stability & Reactivity

10.1 Material Analysis

Reactivity : No Data Available

Chemical stability : Stable Under Normal Circumstances.

Possibility of hazardous reactions : Hazardous polymerization will not occur.

10.2 Environmental

Conditions to avoid : Temperatures above the high flash point of this combustible material in

combination with sparks, open flames, or other sources of ignition.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : Carbon monoxide, Smoke, Carbon monoxide, sulfur oxides, aldehydes, and

other petroleum decomposition products in the case of incomplete combustion. Oxides of nitrogen, phosphorus, calcium, copper, magnesium, sodium, and

hydrogen sulfide may also be present

Section 11 - Toxicological Information

11.1 Toxicological Effects

Ingestion Toxicity : No hazard with normal usage.

Skin Contact: This material is likely to be slightly irritating to skin based on animal data.

Inhalation Toxicity: No data available.

Eye Contact: The material is likely to be irritating to eyes based on animal data.

11.2 Inhalation Toxicity Data					
CAS	Chemical Name	Test	Value	Species	Source
64742-62-7	Residual oils, petroleum, solvent-dewaxed	Inhalation	2.18mg/L	4h Rat	NLM_CIP

Ocean State Waylube 32 Issued: 5/1/2015 Revised: 7/29/2015 Page 5 / 7

Section 11 - Toxicological Information Continued

Sensitizer : No data available to indicate product or components may be a skin sensitizer.

: No data available to indicate product or any components present at greater

than 0.1% is mutagenic or genotoxic.

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria.

Reproductive Toxicity: No data available if components greater than 0.1% may cause birth defects.

Section 12 - Ecological Information

12.1 Aquatic Toxicity

Mutagenicity

Persistence and degradability : No Data Available.

Bioaccumulative potential : Bioconcentration may occur. No Data Available.

Mobility in soil : No Data Available.

Results of PBT and vPvB assessment : Not Determined.

Other adverse effects : No Data Available.

12.2 LC50 Toxicity Data						
CAS	Chemical Name	Test	Value	Species	Source	
64742-58-1	Lubricating oils, petroleum, hydrotreated spent	LC50	79.6mg/L 96h	Brachydanio	IUCLID	
64742-58-1	Lubricating oils, petroleum, hydrotreated spent	LC50	3.2mg/L 96h	Pimephales	IUCLID	
64742-62-7	Residual oils, petroleum, solvent-dewaxed	LC50	5000.0mg/L 96h	Oncorhynchus	IUCLID	
64742-65-0	Distillates, petroleum, solvent-dewaxed heavy paraffinic	LC50	5000.0mg/L 96h	Oncorhynchus	IUCLID	

12.3 Other CAS	Toxicity Data Chemical Name	Test	Value	Species	Source
	Residual oils, petroleum, solvent-dewaxed Distillates, petroleum, solvent-dewaxed heavy paraffinic	EC50 EC50	1000.0mg/L 48h 1000.0mg/L 48h		

Section 13 - Disposal Considerations

13.1 Waste treatment

Waste treatment methods: Dispose of according to Federal, State, Local, or Provincial regulations.

Disposal Methods : Recycle used oil.

Waste Disposal: Use material is non-hazardous according to environmental regulations.

Contaminated packaging: Recycle containers whenever possible!

Section 14 - Transportation Information

14.1 U.S. Department of Transportation (DOT)

14.2. Shipping Description : If shipped by land in a packaging having a capacity of 3,500 gallons or more, the provisions of 49 CFR, Part 130 apply. (Contains oil) International Maritime

Provisions of 45 of 15, Fart 150 apply. (Contains on) international Mantine

Dangerous Goods (IMDG)

14.2. DOT Compliance Note : U.S. DOT compliance requirements may apply. See 49 CFR 171.22, 23 & 25.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable International Civil Aviation Org. / International Air Transport Assoc.

(ICAO/IATA)

14.2. DOT Compliance Requirement: U.S. DOT compliance requirements may apply. See 49 CFR 171.22, 23, 24

Ocean State Waylube 32 Issued: 5/1/2015 Revised: 7/29/2015 Page 6 / 7

Section 15 - Regulatory Information

Agency Inventory Status

(TSCA) Toxic : All components are either listed or not regulated US TSCA Inventory. 64742-65-0 Substance Control Act

64742-62-7 64742-58-1

1

0

WHMIS Hazard Class : None

Canada CPR: This product has been classified in accordance with the hazard criteria

Controlled Products Regulations (CPR) and the SDS contains all the information

required by the Regulations.

CERCLA Sections

302, 313, 372 : This material does not contain reportable chemicals.

311, 312 : Acute Health Hazard No Pressure Hazard No Fire Hazard No

Chronic Health Hazard No Reactive Hazard No

New Jersey Right to Know (NJ RTK)

This material does not contain reportable chemicals.

Massachusets Right to Know (MA RTK)

This material does not contain reportable chemicals.

Pennsylavania Right to Know (PA RTK)

This material does not contain reportable chemicals.

Rhode Island Right to Know (RI RTK)

This material does not contain reportable chemicals.

Section 16 - Other Information

ACGIH American Conference of Governmental Industrial Hygienists

NFPA: HEALTH

CFR Code of Federal Regulations

FLAMMABILITY

DOT United States Department of Transportation

Child Cate Department of Transportation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

NIOSH National Institute for Occupational Safety and Health

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RTK Right-to-Know

SARA Short-term Exposure Limit
TSCA Toxic Substances Control Act

WHMIS Workplace Hazardous Materials Information System

0 0

INSTABILITY

SPECIAL

Disclaimer: This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness.

Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.

Ocean State Waylube 32 Issued: 5/1/2015 Revised: 7/29/2015 Page 7 / 7